



Reg No. : 2003/096209/23 | VAT No. : 4090216435

Steinhoff Industrial Park, George

Bondit™

COLOR: Clear

- BASIC USES:**
- Effective bleed-through blocker over bitumen
 - Adhesive enhancer

PRODUCT DESCRIPTION:

Bondit allows for instant compatibility of Topps Seal® solvent based products over stable black bituminous systems for resurfacing them with rubber durability and the Topps Seal Energy Star® protective layer. Its tenacious adhesive bond to asphalt bitumen on the bottom side also becomes a barrier to asphalt to prevent discoloring the finish coat. The strong chemical affinity of Bondit to Topps Seal on the top is inseparable, making the system complete. Bondit dries in as little as 2 hours for quick project completion.

FEATURES:

- A package that doubles for enhanced adhesion to bitumen and final finish color development
- Spreading Rate: 1 m² / 0.4 – 0.6 liter

**WET MATERIAL
Typical Product
Characteristics**

Color	Milky/Clear
Viscosity	Water Thin
Weight per gallon	4.0 – 4.5 kg.
Solids	36.5% min.
pH	<8.5
VOC	0 g/l
Dry to touch @ 25°C (50% rel. humidity)	2 hours

**CURED COATING
Typical
Performance
Properties**

Ultimate Elongation	750%
Tensile strength	3.8 N/mm ²
Tg	0°C

Water based – do not allow to freeze

The spreading rate (m²/L) is approximate only as it may be influenced by profile, textured or porous surfaces, and application method and tools.