



Reg No. : 2003/096209/23 | VAT No. : 4090216435

Steinhoff Industrial Park, George

ClearSeal™

COLOR: Clear

- BASIC USES:**
- Primes uncoated masonry/concrete
 - Absorbs and binds slight chalkiness
 - Temporary water repellency

PRODUCT DESCRIPTION:

This penetrating clear thin primer prepares porous non-painted masonry and concrete for sealing with Topps Seal® and other coatings. ClearSeal absorbs and bonds light surface oxidation and forms an initial seal beneath the surface. Prepares oxidized surfaces so they may be coated over with excellent adhesion.

FEATURES:

- High resin factor and no fillers
- Strong bonding
- Repels moisture – helps keep dew at surface
- Quick moisture resistance in 1 hour
- Spreading Rate: 1 m² / 0.3 – 0.4 liter

**WET MATERIAL
Typical Product
Characteristics**

Viscosity	Water thin
Weight per gallon	3.2 – 3.4 kg.
Solids	35% min.
Flashpoint of solvent	40°C
VOC	<550 g/l
Dry to touch @ 25°C (50% rel. humidity)	~1 hour
Service Range	-40° - 60°C

The spreading rate (m²/L) is approximate only as it may be influenced by profile, textured or porous surfaces, and application method and tools.