



Reg No. : 2003/096209/23 | VAT No. : 4090216435

Steinhoff Industrial Park, George

GutterGuard®

COLOR: Black

- BASIC USES:**
- Relines, seals, protects gutters and valleys
 - Weather resistant – near zero permeation
 - Blocks rust, moisture, acid rains
 - Seals metal, BUR, modified bitumen, concrete

PRODUCT DESCRIPTION: GutterGuard® bonds tightly, sealing, protecting, lining and restoring gutter interiors to improve flow and help avoid premature replacement. Controlled leveling agents allow the 100% rubber to build a layer of all-rubber protection that keeps water off the original gutter and forms a resistant trough. Additional products pools at the seams, helping to prevent seepage. The resulting smooth surface allows leaves and debris to move easier. This durable compound features tough rubbers that remain pliable, provide extra bonding and abrasion resistance. Tolerates all weather with temperatures down to -40°C. Use Bondit™ to provide enhanced adhesion if applying over bitumen.

- FEATURES:**
- All rubber permanent flexibility
 - Excellent weather, pollution, and acid rain resistance
 - Repels all water – won't wick or transmit moisture
 - Ultimate rust and corrosion protection
 - Spreading Rate: 1 m² / 0.8 liter

WET MATERIAL <i>Typical Product Characteristics</i>	Viscosity	118 – 125 K.U.
	Weight per gallon	3.9 – 4.0 kg.
	Solids	50% min.
	Flashpoint of solvent	40°C
	VOC	<500 g/l
	Dry to touch @ 25°C (50% rel. humidity)	4 hours
CURED COATING <i>Typical Performance Properties</i>	Ultimate Elongation	550%
	Ultimate tensile strength	6.9 N/mm ²
	Peel Adhesion	2.9 pli
	Water vapor permeability	0.25 perms
	Moisture absorption (7 day submersion)	<0.5% max
Service temperature	-40° - 60°C	

The spreading rate (m²/L) is approximate only as it may be influenced by profile, textured or porous surfaces, and application method and tools.